Distoration Rate For Pre Print Plates For .107 Is 96.54%

1 Duro Way Walton, KY 41094 Duro.ArtDepartment@novolex.com CREATED BY: B. Wallrawe

J V Slit Bistro 10 x 6 3/4 x 12

DESIGN GROUP:

Shopper Series

Distoration Rate For Tail Print Plates For .067 Is 97.89%

PLEASE NOTE: All Screen, Half-Tones And Fill All 5 Anti-Bounce Area With Process Jobs Must Be Reviewed By Duro's 40% Screen In All Colors **BORDER DESIGNS** This .020" Mircrodot Is For Flexographic Printing Only. It Should Be Placed On Every Color At The Graphic Printing Division Before Preparing Art. Containing Screens Because Of Machine Movement In Bag Conversion, Copy Should Be Placed At Center Of Largest Copy (Top To Bottom). The Left Microdot Gets Placed 1/64" Inside The Paste Area. Least 1\4" From Fold Lines Or Edges. In The Top Area, Use 1\2" Bleed. This Proof is For Copy, The Right Microdot Gets Placed 1/64" Outside Full Panel Print Border Designs Should Be Kept 1/2" From Fold Edges, Top Cutoff And Bottom Fold. The Right Side Back Fold Edge Line. Must Bleed Into Top & Bottom Panel Of Bag, **Elements And Position Only.** NOT FOR COLOR APPROVAL. Which Is Indicated On Template SCALE: FULL

