Final Art For

CUTOFF

Distoration Rate For Pre Print PLEASE NOTE: This proof is for copy, content, and position **DESIGN GROUP:** BORDER DESIGNS BORDER DESIGNS

Because Of Machine Movement In Bag
Conversion, Copy Should Be Placed At
Least 1/4" From Fold Lines Or Edges.
In The Top Area, Use 1/2" Bleed.

Border Designs Should Be Kept 1/2" From
Fold Edges, Top Cutoff And Bottom Fold. Fill All 5 Anti-Bounce Area With DURO

A NOVOLEX BRAND

1 Duro Way Shopper Series approval only. This proof is not for actual color or 40% Screen In All Colors Containing Screens Plates For .107 Is 97.24% paper substrate used to produce your order. Carefully check all traps (overlap of color) punctuation, spelling, copy and elements. Please use attached approval letter for signed approval. Approval letter, proof and ink roll outs must be returned to produce your order. 1 Duro Way Walton, KY 41094 Macrame Mart 13 x 7 x 17 **Distoration Rate For Tail Print** Duro.ArtDepartment@novolex.com CREATED BY: B. Wallrawe Full Panel Print Must Bleed Into Top & Plates For .067 Is 98.32% Bottom Of Bag. Which Is Indicaated On Template DATE: 2/10/16 SCALE: FULL Starting Web: 41 1/4" Finished Web 41.00" Bleed Copy Must Any Copy Above This Extend To this Line. Line Will Not Be Seen. Face 13.00" Gusset 7.00" Gusset 7.00" Face 13.00" Plates Should Stop / At This Back Fold Line. AFTER CONVERSION, THIS AREA (.25") WILL APPEAR IN BOTTOM OF BAG Holes 3/16" Diameter - 4 1/4" Apart Holes 3/16" Diameter - 4 1/4" Apart

