

Distortion Rate For Pre Print
Plates For .107 Is 97.24%

Distortion Rate For Tail Print
Plates For .067 Is 98.32%




DURO BAG
A NOVOLUX BRAND
1 Duro Way
Walton, KY 41094
Duro.ArtDepartment@novolux.com
CREATED BY: B. Wallrawe
TECHNICAL:
Starting Web: 49 1/4" Finished Web 49.00"

DESIGN GROUP:
Shopper Series
J V Slit Super Royal
14 x 10 x 15
DATE: 2/10/16 SCALE: FULL

PLEASE NOTE: This proof is for copy, content, and position approval only. **This proof is not for actual color or paper substrate used to produce your order.** Carefully check all traps (overlap of color) punctuation, spelling, copy and elements. Please use attached approval letter for signed approval. Approval letter, proof and ink roll outs must be returned to produce your order.

BORDER DESIGNS
Because Of Machine Movement In Bag Conversion, Copy Should Be Placed At Least 1/4" From Fold Lines Or Edges. In The Top Area, Use 1/2" Bleed. Border Designs Should Be Kept 1/2" From Fold Edges, Top Cutoff And Bottom Fold.
Full Panel Print Must Bleed Into Top & Bottom Of Bag, Which Is Indicated On Template

Fill All 5 Anti-Bounce Area With 40% Screen In All Colors Containing Screens



ID # _____
Color _____

Repeat 23.248" 74 Tooth 10 Pitch Gear
Face Height 15.00"
Bottom Fold
Bottom Height 5.748"

Final Art For Plates Should Stop At This Back Fold Line.
TOP CUTOFF
TRIM LINE
TOP FOLD
Artwork Bleeds To This Line To Complete Step & Repeat Of Copy Bleed Into Left Gusset Panel.
CLONE THIS AREA INTO AREA INDICATED AT FAR LEFT OF JOINT (X)

AFTER CONVERSION, THIS AREA (.25") WILL APPEAR IN BOTTOM OF BAG

Bleed Copy Must Extend To This Line. Any Copy Above This Line Will Not Be Seen.