Distoration Rate For Pre Print Plates For .107 Is 97.51%

Distoration Rate For Tail Print

Plates For .067 Is 98.48%

DURO

A NOVOLEX BRAND

1 Duro Way Walton, KY 41094 Duro.ArtDepartment@novolex.com CREATED BY: B. Wallrawe Starting Web: 49 1.4" Finished Web 45.00" DATE: 2/10/16 SCALE: FULL

Printed Flap 13.00"

JV Slit Top Towner

PLEASE NOTE: This proof is for copy, content, and position approval only. This proof is not for actual color or DESIGN GROUP: Shopper Series paper substrate used to produce your order.
Carefully check all traps (overlap of color) punctuation, spelling, copy and elements. Please use attached approval 16 x 6 x 19 1/4 letter for signed approval. Approval letter, proof and ink roll outs must be returned to produce your order.

BORDER DESIGNS Fill All 5 Anti-Bounce Area With Because Of Machine Movement In Bag 40% Screen In All Colors Conversion, Copy Should Be Placed At Containing Screens Least 1/4" From Fold Lines Or Edges. In The Top Area, Use 1/2" Bleed. Border Designs Should Be Kept 1/2" From Fold Edges, Top Cutoff And Bottom Fold. Full Panel Print Must Bleed Into Top &

Bottom Of Bag. Which Is Indicaated On Template

